ELASTOMERIC AND MECHANICAL PROPERTIES OF POLYm-CARBORANYLENESILOXANES. V. THERMAL STABILITY OF SILOXANE ELASTOMERS

Montgomery T. Shaw, et al

Princeton University Princeton, New Jersey

December 1968

ald-10

OFFICE OF NAVAL RESEARCH
Contract No. NOO014-67-A-0151-0011

Task No. NR 056-377

TECHNICAL REPORT NO. 112

ELASTOMERIC AND MECHANICAL PROPERTIES
OF POLY-m-CARBORANYLENESILOXANES. V.
THERMAL STABILITY OF SILOXANE ELASTOMERS

by

M.T. Shaw, A. Blachere, and A.V. Tobolsky

Frick Chemical Laboratory Princeton University Princeton, New Jersey

December 1968



Reproduction in whole or in part is permitted for any purpose of the United States Government.

Distribution of this document is unlimited.

This document has been approved for public release carel order; its distribution is the limit.

Reproduced by the
CLEARINGHOUSE
for Federal Scientific & Technical
Information Springfield Va. 22151

# ELASTOMERIC AND MECHANICAL PROPERTIES OF POLY-m-CARBORANYLENESILOXANES. V. THERMAL STABILITY OF SILOXANE ELASTOMERS

bv

M.T. Shaw, A. Blachere, and A.V. Tobolsky

#### ABSTRACT and INTRODUCTION

Previous reports<sup>1,2</sup> on poly-m-carboranylenesiloxane, or SiB, have emphasized the superior oxidative stability of these systems in comparison with other high temperature elastomers such as silicone rubber. The extreme thermal stability of SiB-2 was illustrated, but not thoroughly explored. Since many applications of high temperature elastomers could conceivably be in oxygen free environments, the desirability of comparative data was evident. This paper reports on a careful comparative study of the thermal stabilities of SiB-2, poly(dimethylsiloxane) and poly(trifluoropropyl methyl siloxane), using the technique of chemical stress relaxation in highly purified nitrogen. The thermal stability of SiB-2 is quite outstanding in this test.

## EXPERIMENTAL

#### Materials:

The silicone rubber and SiB-2 elastomers were identical to those described in Part III.<sup>2</sup> The poly(trifluoropropyl methyl siloxane), or Silastic, was kindly supplied by T. D. Talcott of the Dow Corning Co., Midland, Michigan. The filled and unfilled Silastics were cured for 15 minutes at 260°F using 2% benzoyl peroxide. All samples were extracted with benzene and vacuum dried before use.

#### Instrumental:

The relaxometers used to measure thermal stability are described elsewhere.<sup>3</sup> An effort was made to expose all samples to the same conditions before and during the relaxation experiments. Thus all samples were exposed to 99.996% nitrogen at 100°C for at least 16 hours in the relaxometer, after which the temperature of the sample was increased to the temperature of the experiment, and held for one hour. The sample was then extended less than 10%, and the resulting force was measured as a function of time.

### RESULTS AND DISCUSSION

The rate of force decay during a high temperature relaxation experiment in an inert atmosphere is a highly sensitive measure of the thermal statility of the network chains which must carry the load. The parameter used to characterize the rate of relaxation is the chemical relaxation time,  $\tau_{\rm ch}$ , which is the time required for the relative stress in the sample to fall to 1/e = 36.8%. Values for  $\tau_{ch}$  taken from Figures 1-5 are listed in Table 1 for the temperatures at which the various elastomers were tested. It is significant that SiB-2 outperforms the Silastic and silicone rubbers by about two orders of magnitude, dramatically confirming the high stability conferred to the siloxane linkage by the carborane units present in the main chains. The trifluoropropyl side groups of the Silastic elastomer do not enhance the thermal stability of the siloxane linkage (their purpose is mainly to increase solvent resistance.) The presence of filler (mostly silica) gives added thermal stability to these elastomeric systems with the exception of SiB-2 where there is no effect. There is good evidence that this may be due, in part, to an increased rate of crosslinking at high temperatures in the presence of filler.2


The apparent activation energies of relaxation, obtained from plots of  $\ln \tau_{\rm ch}$  vs 1/T are also listed in Table 1. A high apparent activation energy does not imply a stable elastomer.


TABLE I


Chemical Relaxation Times and Apparent Activation Energies for Siloxane Elastomers in Nitrogen


 $(\tau_{\rm ch} \text{ seconds}) \times 10^{-4}$ 


Polymer	Figure	300°C	325°C	350°C	E*, kcals/mole
Silicone Rubber	1	0 <b>.3</b> 6	0.23	0.15	12
Silastic 420	2				
unfilled		0.15	0.035		40
Silastic L5-53	3				
filled		0.40	0.15	0.034	40
SiB-2, unfilled	4	> 14	8.3	5.2	15
SiB-2, filled	5	> 12	6.3	2.5	22











## References

- 1. L.H. Sperling, S.L. Cooper, and A.V. Tobolsky, J. Appl. Polymer Sci., 10, 1725 (1960).
- 2. E.J. Zaganiaris, L.H. Sperling, and A.V. Tobolsky, <u>J. Macromol. Sci.-Chem.</u>,  $\underbrace{\text{Al}}_{(\epsilon)}$ , 1111 (1  $\epsilon$ ?).
- 3. M.T. Shaw and A.V. Tobolsky, Technical Report No. 111, Office of Naval Research.

Unclassified						
Security Classification						
DOCUMENT CONTROL DATA - R & D  Security s has alreation of title, body of abstract and indexing annotation must be entered when the assertal report is a basisfied.						
1 ORIGINATING ACTIVITY (Corporate author)	WINEFORT SECURITY CLA SILICATION					
Frick Chemical Laboratory	. Unclassified					
Princeton University	2b. GROUP					
Princeton, New Jersey 08540						
ELASTOMERIC AND MECHANICAL PROPERTIES OF POLY-m-CARBORANYLENESILOZAMES V. THERMAL STABILITY OF SILOXANE ELASTOMERS						
4 DESCRIPTIVE NOTES (Type of report and inclusive dates)						
Montgomery T. Shaw Albert Blachere Arthur V. Tobolsky	• •					
REPORT DATE	78. TOTAL NO OF PAGES /b. NO OF REES					
December 1968	10 3					
NOOO14-67-A-0151-0011  PROJECT NO  NR 056-377	98. ORIGINATOR'S REPORT NUMBERIS) RLT-112					
c.	9b. OTHER REPORT NO(\$) (Any other numbers that may be assigned					
	this report)					
d.						
Qualified requesters may obtain copies	s of this report from DDC					
II SUPPLEMENTARY NOTES	12 SPONSORING MILITARY ACTIVITY					
	Office of Naval Research					
13 ABSTRACT	<u> </u>					
The thermal stabilities of elastomers based on poly(dimethyl silozane), poly (trifluoropropyl methyl silozane) and poly-m-carboranyl siloxane, represented by SiB-2, were compared by the technique of chemical stress relaxation in nitrogen. Filled and unfilled elastomers were tested in the temperature range of 300-350°C. The SiB-2 elastomers showed chemical relaxation times which were 50-100 times greater than the other elastomers, illustrating their outstanding thermal stability.						
₩						

DD FORM 1473 (PAGE 1)

Unclassified
Security Classification

S/N 0102-014-6600

Security Classification ROLE ROLE WT Siloxane Elastomers SiB Elastomers Thermal Stability Chemical Stress Relaxation

DD . FORM . 1473 (BACK)
(PAGE 2)

Unclassified

Security Classification